



Groundsmaster® 4000-D/4010-D Specifications*

GROUNDMASTER 4000-D, MODEL 30448 / GROUNDMASTER 4010-D, MODEL 30446											
ENGINE	Kubota® V2403-M-T, 4-cylinder, liquid-cooled, turbo-charged diesel. 148.5 cu. in. (2.4 liter) displacement. Engine rated at 60 hp (45 kW) gross, 58 hp (43.3 kW) net and 125 ft.-lbs. torque at 2,000 rpm. 10 quart (9.5 liter) oil capacity.										
AIR CLEANER	Dry, replaceable primary and safety elements.										
RADIATOR	Rear-mount, 2 pass cross-flow, 7-row, 5 fins per inch, 13 quart (12.3 liter) capacity.										
FUEL CAPACITY	19 gallons (72 liters) diesel fuel. Biodiesel-Ready for use up to B-20 (20% biodiesel and 80% petrol blend).										
TRACTION DRIVE	Full-time, bi-directional, hydrostatic, closed-loop, 4WD transmission. Variable displacement piston pump with servo control powers fixed displacement piston motors which drive single reduction planetary gear assemblies at each front wheel. Parallel hydraulic flow powers fixed displacement piston motor which drives mechanical axle in rear. 2WD in forward (transport) range.										
HYDRAULICS/COOLING	8 gallon (30.3 liter) capacity with 2 micron remote spin-on filter. 19 row, single pass cooler that tilts out for cleaning. Variable speed radiator cooling fan with automatic (based on coolant and oil temps) and manual reversing capabilities.										
DIAGNOSTICS	Diagnostic pressure test ports: forward and reverse traction, left, center and right decks, reverse 4WD, lift, steering, charge and deck counterbalance circuits.										
GROUND SPEED	Transport: 0-15 mph (0-24.2 km/h) forward, 0-9 mph (0-14.4 km/h) reverse. Mow: 0-8 mph (0-12.4 km/h) forward, 0-4 mph (0-6.4 km/h) reverse.										
TIRES	Front: 26 x 12-12, 6-ply tubeless Multi-Trac. Rear: 20 x 10-10, 6-ply tubeless Multi-Trac.										
MAIN FRAME	All welded formed-steel frame with integral tie-down anchors.										
BRAKES	Mechanically actuated, internal wet disc brakes on input to each planetary drive. Individual foot-operated steering brake control of left and right wheel. Lock pedals together and latch to engage parking brake.										
SEAT	4-way adjustable, right armrest travels with seat and suspension.										
STEERING	Power steering with dedicated power source. Steering wheel tilts to desired operator position.										
GAUGES	Hour meter, fuel gauge, engine temperature gauge. Indicator lights for high temperature, oil pressure, alternator and glow plugs. Audible alarm for low oil pressure and high coolant temperature.										
CONTROLS	Tilt steering, ignition switch, throttle, foot-operated traction pedal, lockable individual brake pedals, parking brake lock, mow/transport speed selector switch, 3-two position switches for individual deck lift/lower, counterbalance adjustment, tow valve, cup holder, toolbox, radio holder, fan switch and 12-volt power outlet.										
ELECTRICAL	12-volt, 690 cold cranking amps battery, 40 amp alternator. Overload protection with automotive type fuses.										
INTERLOCKS	Prevents engine from starting unless traction pedal is in neutral and deck is disengaged. If operator leaves seat with deck engaged, engine stops. Mowing only permitted in low range. Engine stops if parking brake engaged and traction pedal not in neutral. Deck transport latches.										
GROUND CLEARANCE	6.5" (16.5 cm)										
OVERALL DIMENSIONS	<table border="1"> <thead> <tr> <th>Height</th> <th>Length</th> <th>Width</th> <th>Transport Width</th> <th>Wheelbase</th> </tr> </thead> <tbody> <tr> <td>81" (206 cm) w/ROPS</td> <td>135" (343 cm) w/decks down</td> <td>136" (346 cm) w/decks down</td> <td>71" (180 cm) @ 2" (5 cm) HOC</td> <td>55.5" (140 cm)</td> </tr> </tbody> </table>	Height	Length	Width	Transport Width	Wheelbase	81" (206 cm) w/ROPS	135" (343 cm) w/decks down	136" (346 cm) w/decks down	71" (180 cm) @ 2" (5 cm) HOC	55.5" (140 cm)
Height	Length	Width	Transport Width	Wheelbase							
81" (206 cm) w/ROPS	135" (343 cm) w/decks down	136" (346 cm) w/decks down	71" (180 cm) @ 2" (5 cm) HOC	55.5" (140 cm)							
WEIGHT	4,166 lbs. (1889 kg) w/ full fluids (GM4000). 4,595 lbs. (2089 kg) w/ full fluids (GM4010).										
FUEL ECONOMY (4000)**	Acres per Gallon - 5.0 Mowing Range - 12.1 hours Fuel Consumption - 1.57 Gal/Hr (5.95 L/Hr)										
SAFETY CAB (4010)	Factory installed, ROPS certified, climate controls (AC & heating), opening front and rear windows, exterior front wiper/washer, interior mirror, exterior side mirrors, 4-way flashers and turn signals.										
SAFETY	Complies with American National Standards Institute (ANSI B71.4-2004) and applicable CE (machine directive 89/392, 91/368, 93/44, 84/538, 89/336) requirements.										
WARRANTY	Two-year limited warranty. Refer to Operator's Manual for further details.										
ACCESSORIES	Work light kit model 30442 (Consists of dual taillights, dual headlights, slow moving vehicle sign, turn signal, flasher and lights). Cruise control kit - model 30421, sunshade - model 30359, rotary broom - model 30426										
CUTTING DECKS											
WIDTH OF CUT	Overall: 132" (335 cm), Front: 62" (157.5 cm), Wings: 42" (106.7 cm), Overlap: 7" (12.8 cm).										
MOWING RATE	Mows up to 10.6 acres/h (4.3 hectares/h) at 8 mph (12.4 km/h) (assumes no overlap or stops).										
CONSTRUCTION	Welded steel with steel channel and plate reinforcements.										
DECK DRIVE	Direct mounted hydraulic motor into spindle. Remaining spindle(s) driven by individual B section kevlar belt. Quick release belt covers.										
HEIGHT-OF-CUT	1"-5" (25-127 mm) in .5" (13 mm) increments.										
SPINDLES	1.25" (3.17 cm) diameter spindle shafts, 9" (22.9 cm) diameter conical ductile iron housing, and 2 greaseable tapered roller bearings.										
BLADES	21.75" (55.2 cm) long, 2.5" (6.4 cm) wide, .25" (.64 cm) thick.										
CASTER WHEELS	8 x 3.50-4, 4-ply, smooth, pneumatic, sealed precision ball bearings.										
GROUND FOLLOWING	6" anti-scalp cups on each blade, adjustable skids on each deck, 4 anti-scalp rollers on front deck and 1 on each wing.										
WING PROTECTION	Bi-directional, impact absorption device on each wing deck.										
RECYCLER® KIT	Model 30420 will convert decks into Guardian® Recycler® decks.										
MULCHING KIT	Model 30422.										

*Specifications and design subject to change without notice.

**Dependent on operator and turf conditions.

The Groundsmaster 4000-D & 4010-D are manufactured in Tomah, WI ISO 9002 Certified Plant.





Groundsmaster® 4000-D Attachment Specifications*



DEBRIS BLOWER, MODEL 30425	
FAN OUTPUT	5000 cfm, 165 mph.
OUTLET	Adjustable outlet opening, 39-70 in' (251.6-451.6 cm).
DIRECTIONAL CONTROL	90° outlet deflector operated from seat.
HEIGHT ADJUSTMENT	4"-6.5" (10.2-16.5 cm). Adjustment is with .5" (1.3 cm) spacers and holes in castor fork.
CASTOR WHEELS	Two 8" (20.3 cm) x 3.5" (8.9 cm) solid rubber tires.
TRANSPORT GROUND CLEARANCE	11.25" (28.6 cm)
FAN SPEED	2575 rpm
FAN	Backward curved, cast aluminum (356-T6 material) fan. 12 blades per side, 21" (53.3 cm) outside diameter, 6.375" (16.2 cm) width, 34 lbs. (15.4 kg).
FAN HOUSING	10-gauge steel face plates welded to 14-gauge wrapper. Eight degree increasing scroll from cutoff.
FAN DRIVE	Gear motor directly coupled to fan shaft via Rotex coupling. 1.25" (3.2 cm) diameter fan shaft rotates on 2 greaseable ball bearings.
WEIGHT	321 lbs. (145.7 kg)
OPTIONS	180° deflector kit P/N 95-5909.
ROTARY BROOM, MODEL 30426	
BRUSH FILAMENT MATERIAL	Virgin polypropylene, high carbon wire, or a combination of both.
BRUSH DIAMETER	Uses 24" (61 cm) brush elements.
OSCILLATION ANGLE	8°
SWEEPING WIDTH ANGLE	Brush swings 25° in both directions, 70.5" (179 cm) sweeping width at center position, 64" (162.6 cm) minimum sweeping width at full swing left or right.
CASTOR WHEELS	Two 8.0" x 3.5" (20.3 x 8.9 cm) pneumatic rubber tires.
GROUND CLEARANCE	6" (15.2 cm)
BRUSH SPEED	220 rpm, no load.
BRUSH GROUND PRESSURE ADJUST	Adjustment is .5" (1.3 cm) spacers and holes in castor fork.
HYDRAULIC/MECHANICAL BRUSH DRIVE	Ross 6.10 cubic inch roller vane motor drives directly into 16 tooth sprocket. 40 tooth sprocket mounts on brush shaft. One 60# chain connects motor and brush.
BRUSH SWING CONTROL	A 2" (2.1 cm) bore, 15" (38.1 cm) stroke, swing cylinder is connected in parallel with hydraulic brush drive. The cylinder is controlled by a 3-position, closed center, 4-way solenoid directional valve. A 6 mm grade 8.8 shear bolt connects rod end of cylinder to 4-bar linkage.
ELECTRICAL CONNECTION	Wire harness kit required – P/N 95-3263.
WEIGHT	567 lbs. (257.4 kg).
OPTIONS	High carbon wire brush filament P/N 95-5942. Deflector kit P/N 95-7496.
SUNSHADE	
UNIVERSAL MOUNT	Model 30359

*Specifications and design subject to change without notice.

The Groundsmaster 4000-D is manufactured in Tomah, WI ISO 9002 Certified Plant.





Groundsmaster® 4000-D Attachment Specifications*



	SNOWTHROWER ERSKINE MODEL 2000**
STAGE	2
WIDTH OF CUT	61" (155 cm)
CUTTING HEIGHT	29" (74 cm)
CUTTING EDGE	3/8" x 3" (9.5 mm x 7.6 cm) bolt-on
SKID SHOES	Adjustable
AUGER DIAMETER	16" (41 cm) open flight
FAN DIAMETER	20" (51 cm) 4-blade
CHUTE ROTATION	Hydraulic 270°
SHEAR PROTECTION	Pressure relief
CASTING DISTANCE	Up to 30' (9.14 m)
APPROXIMATE SHIPPING WEIGHT	850 lbs. (386 kg)
HOSES	Included

*Specifications and design subject to change without notice.

**Manufactured by Erskine. The Toro Company does not manufacture or sell the snowthrower, nor does Toro guarantee these accessories in any manner whatsoever.

